

One Unit, Total Control

KEY FEATURES

 Controller for Ethernet interfaced devices, and other PS-Data devices (WV-CU650 is only for RS-485.)

Integrated System Control

Camera Control

- Detached joystick controls Pan/Tilt and Zoom, allowing seamless tracking.
- Larger numeric keypad provides direct access to cameras.

Recorder Control

- Jog Dial and Shuttle Ring for smoother recorder control
- Dedicated Record, Play, and Search buttons

Switcher Control

· Image switching and sequencing buttons

Easy to Operate While Focused on Surveillance

Universal Design for Right or Left Hand Use

- Detached joystick pad
- · Layout with Jog Dial and Shuttle Ring in centre

More Comfortable Extended Surveillance

- · Soft padding on joystick
- Adjustable joystick height for large or small hands
- Low centre of gravity design and adjustable angle minimize strain

Instinctive Operation

Cockpit style button layout


System Management Capability

- User level management for registered users
- User assignable buttons: four in main unit plus three in palm rest
- Setup data of WV-CU950/CU650 can be transferred via RS-485 to another WV-CU950/CU650.

SPECIFICATIONS

Model No.	WV-CU950	WV-CU650
Power Source (using the supplied AC adaptor)	9 V DC, 600 mA	9 V DC, 300 mA
Power Source (supplied AC adaptor)	230 V AC, 50 Hz, 150 mA	
Ethernet Port	10Base-T/100Base-TX, RJ-45 x 1	_
Data Output/Input Port	6-conductor modular jack (RS-485, Full duplex) x 2	
Serial Port	9pin D-sub connector	
Controller Number	1 to 8 (rotary switch)	
Ambient Operating Temperature	-10 °C to +50 °C	
Unit Number Selection	1 to 99	
Monitor Number Selection	1 to 99	
Camera Number Selection	1 to 256	
Dimensions (W x H x D)	Main Unit: 290 x 111 x 221 mm, 3D Joystick Unit: 134 x 146 x 218 mm	
Weight (without the AC adaptor)	Main Unit: 1.3 kg, 3D Joystick Unit: 0.8 kg	

MAJOR OPERATING CONTROLS



- Operation Indicator
- Alarm Suspend Indicator

- Clear Button Alarm Reset/Alarm All Reset Button
- Alarm Heset/Alarm All Heset Butt
 Alarm Acknowledge Button
 Alarm/Alarm Suspend Button
 Camera Function/
 System Function Button
 Alarm Recall Button

- On-Screen Display Button
- 12 Monitor Lock/Logout Button
- (3 Tour Sequence/ Group Sequence Button
- Sequence Pause/
 Sequence Stop Button
- (5) Go To Last Button
- 6 Electronic Zoom Button
 Multiscreen Selection B
- Multiscreen Selection Buttor 18 Mark Button

- 22 Defroster Button 49 Enter butto
 23 Wiper Button 46 Feet
 24 Stop Button 46 Serial Port
 25 Play/Pause Button 46 Serial Port
 26 Recording Button 47 Data Ports
 27 Shuttle Ring (Outside)/JogDial (Inside) 48 Mode Select
 28 Shuttle Hold Button 49 Controller N
 29 DC W Jone
 20 DC W Jone
 20 DC W Jone
 20 DC W Jone
 21 DC W Jone
 22 DC W Jone
 23 DC W Jone
 24 DC W Jone
 25 DC W Jone
 26 DC W Jone
 26 DC W Jone
 26 DC W Jone
 27 DC W Jone
 28 DC W Jone
 28 DC W Jone
 29 DC W Jone
 20 DC W J
- 29 History Button 30 Button 31 + Button
- Recorder/Unit Selection Button Preset/Program Preset Button Camera Position Button

- 39 Numeric Buttons 39 Monitor/Escape Button
- 37 Camera/Set Buttor 38 LCD
- 39 Adjustment Button

- Auxiliary 2 ON/OFF Button
 Auxiliary 1 ON/OFF Button
 Auxiliary 1 ON/OFF Button
 Search/Time and Date Search Button
 Setre Button
 Search Button
 Search Button
 Search Button
 - 43 Enter Button 44 Feet
 - 45 Joystick Connector 46 Serial Port

 - ction Switches
 - Gentroller Number Switch
 DC 9V Input Jack
 Top Button
 Zoom Wheel Controller

 - Iris Control Buttons
 Focus Control Buttons

 - 55 A and B Buttons 56 3D Jovstick

 - Adjusting Screw
 10Base-T/100Base-TX Port
 - (WV-CU950 only)

DIMENSIONS

